

# ExStik<sup>®</sup> Waterproof Chlorine Meter

**Direct reading of Total Chlorine down to 0.01ppm**  
Unaffected by color/turbidity of the sample

## Features:

- Direct reading of Total Chlorine provides fast and easy measurements (less than 2 minutes)
- Low detection limit down to 0.01ppm
- Wide dynamic range of measurement up to 10ppm (use dilution method for 10 to 50ppm)
- Unaffected by sample color or turbidity
- Automatic electronic calibration
- Memory stores, tags and recalls up to 15 readings
- Unique flat surface chlorine electrode
- Waterproof to IP67 standard
- The state of the art LCD simultaneously displays ppm of Total Chlorine and Temperature plus analog bargraph indicator
- Complete with meter and flat surface Chlorine electrode, ExTab<sup>®</sup> reagent tablets (50 tests), protective sensor cap, sample cup with cap, four 3V CR-2032 batteries, and 48" (1.2m) neckstrap



Patent Pending



Testing Chlorine level in public reservoir

ExTab<sup>™</sup> Chlorine Reagent tablets

3 (20mL) ampules of Chlorine Standard

## Ordering Information:

- CL200.....ExStik<sup>®</sup> Chlorine Meter  
 CL203.....ExTabs<sup>™</sup> Reagent tablets (10pk - 100 tests)  
 CL204.....ExTabs<sup>™</sup> Reagent tablets (100pk - 1000 tests)  
 EX006.....Weighted base with 5 solution cups  
 EX007.....Spare sample solution cups (24pk)  
 CL205.....Spare Chlorine electrode  
 PH105.....Spare pH electrode  
 RE305.....Spare ORP electrode  
 CA903.....Carrying case for ExStik<sup>®</sup> kit  
 CL207.....Chlorine standard (1ppm) -3 ampules (20 mL each)  
 CA895.....Carrying Case, Small with Belt Loop  
 EX010.....Extension Cable, 3ft (1 Meter) with probe weight for ExStik  
 EX050.....Extension Cable, 16ft (5 Meters) with probe weight for ExStik  
 PH115.....Spare Probe. pH, Refillable Reference  
 RE305.....Spare Probe, ORP  
 EX800.....ExStik 3-in-1 Kit (Chlorine, pH, Temp)  
 EX900.....ExStik 4-in-1 Kit (Chlorine, pH, ORP, Temp)

Specifications	
ppm	0.01 to 10.00ppm (10 to 50ppm using dilution method)
Temperature	23° to 194°F (-5 to 90°C)
Resolution	0.01ppm ; 0.1°F/°C
Accuracy	±10% of reading ±0.01ppm; ±1.8°F/±1°C
Power	four SR44W button batteries
Dimensions/Weight	1.4 x 6.8 x 1.6" (35.6 x 172.7 x 40.6mm)/ 3.85oz (110g)

