



EV9607-03

# 70F Cartridge

Problem solving and special application cartridge



70F Replacement Cartridge: EV9607-03

## BENEFITS

- Oxidizing water filter for iron and sulfur in low water volume applications
- Removes noxious tastes and odors by oxidizing dissolved iron, sulfur and manganese (up to 10 ppm)
- Reduces corrosion in coffee brewers, fountain equipment and water coolers
- Reduces metallic tastes and sulfur (rotten egg) tastes
- Reduces metallic stains
- pH range: 6.6 to 8.8

## INSTALLATION TIPS

- Install vertically with cartridge hanging down
- Allow 2-1/2" clearance below the cartridge for easy cartridge replacement
- Flush cartridge by running water through filter for three minutes at full flow
- Follow with submicron precoat filtration

## OPERATION TIPS

- Change cartridges on a regular 6 month preventative maintenance program
- Change cartridges when capacity is reached or when pressure falls below 10 psi
- Always flush the filter cartridge at time of installation and cartridge change

## APPLICATION/SIZING

- Problem solving and special application cartridge for extraordinary water conditions
- Capacity: 1,000 ppm gallons
- To determine cartridge life, divide total capacity of cartridge (1,000 ppm gallons) by the iron or hydrogen sulfide content of the water
- i.e. one cartridge will treat up to 200 gallons of water having an iron content of 5 ppm (1000 divided by 5 = 200)

# 70F Cartridge

## SPECIFICATIONS

**Overall Dimensions:**  
20.75"H x 3.25"Diameter

**Service Flow Rate:**  
Maximum 0.5 gpm (1.9 Lpm)


**Pressure Requirements:**  
10 - 125 psi (0.7 – 8.6 bar), non-shock

**Temperature:** 35 - 100°F (2 - 38°C)

No electrical connection required

**Contents:** Granular of manganese green sand

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.



## WARRANTY

Everpure water treatment systems (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.

### EVERPURE®

*Worldwide Headquarters:*  
EVERPURE, LLC  
1040 Muirfield Drive  
Hanover Park, Illinois 60133  
Toll Free (800) 323-7873  
Tel (630) 307-3000  
Fax (630) 307-3030  
<http://www.everpure.com>

*In Europe:*  
Pentair Water Belgium B.V./B.A.  
Industriepark Wolfstee  
Toekomstlaan 30  
B- 2200 Herentals  
BELGIUM  
TEL: +32.(0).14.283.500  
FAX: +32.(0).14.283.505

*In Japan:*  
Hashimoto MN Bldg. 7F  
3-25-1 Hashimoto Sagamihara-Shi  
Kanagawa 229-1103  
JAPAN  
TEL: 81.(0)42.775.3011  
FAX: 81.(0)42.775.3015