SMF Espresso 7500

SYSTEM PART: #82-1600

Replacement Cartridge: #108-600

RATED CAPACITY (GALLONS) @ 5 GPM: CHLORINE *: 10,000

Chloramine *: 3,000

SCALE REDUCTION (GALLONS): 7,500

FLOW RATE: 1 GPM

Min./Max. Pressure: 40–125 psi

MIN./MAX. TEMP.: 40°-100° F

Inlet/Outlet Size: 1/2" Barb Standard

17 Modular Fittings Available

SHIPPING WEIGHT: 19 Lbs. Dimensions (W/D/H): 14/9/ 19"





- INHIBIT SCALE BUILD-UP
- REDUCE PITTING OF HEATING ELEMENTS IN COFFEE/TEA Brewers
- IMPROVE TASTE OF BREWED BEVERAGES
- Provide Safe, Clean Ingredient Water
- REDUCE CHLORINE, CHLORAMINE, BAD TASTES AND ODORS, TOTAL ORGANIC COMPOUNDS, TANNINS AND TRIHALOMETHANES

COFFEE,

TEA & ESPRESSO

APPLICATIONS

FOR: SCALE REDUCTION, CHLORINE,

CHLORAMINE, SEDIMENT, THMS,

Organics, Tannins, Bad Taste and Odor Reduction

VOLUME: LOW-MEDIUM

FILTER BENEFITS:

- One filter can do it all: dirt reduction, chemical reduction, chloramines reduction and Scale Reduction! No pre-filter required!
- The first Jumbo Sanitary Filter on the Market!
- Nylon construction to withstand high pressure!
- FILTER PERFORMANCE GUARANTEE!
- 40 TIMES MORE DIRT HOLDING CAPACITY THAN CONVENTIONAL CARBON BLOCK FILTERS AND OTHER POLYPROPYLENE SEDIMENT FILTERS!
- 30 TIMES THE CHLORAMINE REDUCTION OF A CONVENTIONAL CARBON BLOCK!
- Low pressure drop!
- \bullet Modular filter design for up to 50% less installation time!
- QUICKLY ADD FITTINGS FOR EXTRA FILTER CAPACITY WITH NO TOOLS REQUIRED!

TECHNOLOGY:

- CERAMIC MATRIX WITH ULTRA HIGH POROSITY CARBON
- NanoCRYSTAL

APPLICATIONS:

- Coffee Brewers
- Tea Brewers
- Espresso & Cappuccino Machines





Base system has been tested and certified by NSF International against ANSI/NSF Std. 42. Please visit www.nsf.org for specifications.

Do not use with water that is microbiologically unsafe or of unknown quality.

