

# SMF IC600

SYSTEM PART:	#80-6100
REPLACEMENT CARTRIDGE:	#108-010
RATED CAPACITY (GALLONS) @ 5 GPM:	CHLORINE *: 50,000 CHLORAMINE: 15,000
FLOW RATE:	2.5 -5 GPM
MIN./MAX. PRESSURE:	40- 125 PSI
MIN./MAX. TEMP.:	40°- 100° F
INLET/OUTLET SIZE:	1/2" BARB STANDARD
	17 MODULAR FITTINGS AVAILABLE
SHIPPING WEIGHT:	16 LBS.
DIMENSIONS (W/D/H):	14/9/19"

## FOUNTAIN APPLICATION

FOR: CHLORINE, CHLORAMINE, SEDIMENT, THMS, ORGANICS, TANNINS, BAD TASTE AND ODOR REDUCTION

VOLUME: MEDIUM



### SPECIFIED TO:

- IMPROVE TASTE OF FOUNTAIN BEVERAGES
- PROVIDE SAFE, CLEAN INGREDIENT WATER
- REDUCE CHLORINE, CHLORAMINE, BAD TASTES AND ODORS, TOTAL ORGANIC COMPOUNDS, TANNINS AND TRIHALOMETHANES
- INCREASE FOUNTAIN SALES
- INCREASE CARBONATION

### FILTER BENEFITS:

- ONE FILTER CAN DO IT ALL: DIRT REDUCTION, CHEMICAL REDUCTION AND CHLORAMINES REDUCTION! NO PRE-FILTER REQUIRED!
- THE FIRST JUMBO SANITARY FILTER ON THE MARKET!
- NYLON CONSTRUCTION TO WITHSTAND HIGH PRESSURE!
- FILTER PERFORMANCE GUARANTEE!
- 40 TIMES MORE DIRT HOLDING CAPACITY THAN CONVENTIONAL CARBON BLOCK FILTERS AND OTHER POLYPROPYLENE SEDIMENT FILTERS!
- 30 TIMES THE CHLORAMINE REDUCTION OF A CONVENTIONAL CARBON BLOCK!
- LOW PRESSURE DROP!
- MODULAR FILTER DESIGN FOR UP TO 50% LESS INSTALLATION TIME!
- QUICKLY ADD FITTINGS FOR EXTRA FILTER CAPACITY WITH NO TOOLS REQUIRED!

### TECHNOLOGY:

- ULTRA HIGH POROSITY CARBON WITH MICRO-STRUCTURE

### APPLICATIONS:

- 1 TO 2 CARBONATORS
- FOUNTAIN AND MULTIUSE APPLICATION SUCH AS COFFEE, TEA AND JUICE

\* Independently tested by an E.P.A. approved laboratory to ANSI/NSF Standard 42 specifications for the reduction of Particulate Class II, Chlorine, Chloramine, Taste and Odor.



System has been tested and certified by NSF International against ANSI/NSF Std. 42. Please visit [www.nsf.org](http://www.nsf.org) for specifications.

Do not use with water that is microbiologically unsafe or of unknown quality.

**selecto** 

3980 LAKEFIELD COURT, SUWANEE, GA 30024 USA  
800-635-4017 • 678-475-0799 • [WWW.SELECTOINC.COM](http://WWW.SELECTOINC.COM)

© 2007 Selecto Scientific, Inc. • All Rights Reserved.

805-001 Rev. 03-21-07